

1515RCN

Precious metal commutation

Applications: Precision driving field in medical, health care, automobile, industrial automation, etc.

Characteristics

			-4P-3.0	
1	Voltage	V	3.0	
2	Terminal resistance	Ω	6.1	
3	No-load speed	rpm	6200	
4	No-load current	mA	10	
5	Stall torque	mNm	2.2	
6	Stall current	mA	490	
7	Nominal torque	mNm	0.6	
8	Nominal speed	rpm	4650	
9	Nominal current	mA	130	
10	Max. output power	W	0.36	
11	Max. efficiency	%	75	
12	Back-EMF constant	mV/rpm	0.5	
13	Torque constant	mNm/A	4.5	
14	Speed/torque gradient	rpm/mNm	2800	
15	Rotor inertia	gcm ²	0.21	
16	Weight	g	14.2	
17	Thermal resistance housing-ambient	K/W	32.1	
18	Thermal resistance winding-housing	K/W	26.3	
19	Thermal time constant motor	s	130	
20	Thermal time constant winding	s	9	
21	Operating temperature range	°C	-20~+85	
22	Max. winding temperature	°C	85	
23	Axial play	mm	≤ 0.3	
24	Radial play	mm	0.012	
25	Axial load dynamic	N	0.15	
26	Axial load static	N	15	
27	Radial load at 3 mm from mounting face	N	0.4	
28	No. of pole pairs		1	
29	Bearings		2 sleeve bearings	
30	Commutator		metal 5 segments	
31	Protection class		IP 30	

Options

- Lead wires length
- Shaft length
- Special coils
- Gearheads

Outline Drawing

